

2.0 SERIES VALVING SPECIFICATIONS

COMPRESSION DAMPING

VALVE OUTSIDE DIA.	#30	#35	#40	#45	#50	#55	#60	#65	#70	#75	#80	#85	#90
1.600"	0.008	0.008	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015
1.425"	0.008	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015
1.350"	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015
1.100"	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015
.950"	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015
.800"	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020

REBOUND DAMPING

VALVE OUTSIDE DIA.	#30	#35	#40	#45	#50	#55	#60	#65	#70	#75	#80	#85	#90
1.425"	0.008	0.008	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015
1.350"	0.008	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015
1.100"	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015
.950"	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015
.800"	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015
.750" BACK UP	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200

